

FO Number / OM Number		Print date
2619-12-63866 / 21263866		2023-06-06
Chassis Number	VIN Number	
BB-376107	YV2RT40AXNB376107	
Build week (YYWW)	Confirmed delivery day	Planned arrival date
202205	2022062 (YYYYWWD)	
Latest update		
2022-03-06 (YYYY-MM-DD)		
Updated Delivery Date		
2022075 (YYYYWWD)		

Chassis Unique Homologation Document	General Homologation Document
LEGCHECK	<ul style="list-style-type: none"> Volvo Powertrain RMI statement Volvo Truck RMI statement COP Statement

Supplementary drawing(s):
<ul style="list-style-type: none"> FRONT MOUNTED EQUIPMENT. RADAR ZONE. FH BUMP-B-B2 front radar keep-out-zone.zip FH BUMP-B-B2 front radar keep-out-zone.jpg POWER TAKE-OFF 22885846_01.dxf.zip 22885846_01.pdf CAB-HSLP 23339406_03.zip 23339406_03.pdf Supplementary Drawing 23339406_04.zip 23339406_04.pdf Supplementary Drawing 23339406_05.zip 23339406_05.pdf Supplementary Drawing 23921563_02.zip 23921563_02.pdf REAR FENDER 3200301.dxf 3200301.pdf BODY ATTACHMENT 3200308_03.dxf.zip 3200308_03.pdf TRAILER CONNECTION 3200309_3.dxf.zip 3200309_3.pdf AIR INTAKE 3200336.dxf 3200336.pdf AD-BLUE TANK 3200344_03.zip 3200344_03.pdf UNDERRUN PROTECTION FRONT 3200346.dxf 3200346.pdf EXHAUST SYSTEM 3200372_02.dxf.zip 3200372_02.pdf UNDERRUN PROTECTION, SIDE 3200383_3.dxf.zip 3200383_3.pdf
BEP, chassis unique drawing in scale
General chassis drawing:
<ul style="list-style-type: none"> FH42T3A_2147.dxf.zip FH42T3A_2147.pdf
Data Sheet : none found

Tyres front	Tyres rear
315/70R22.5 GOODYEAR FUELMAX PERFORMANCES	315/70R22.5 GOODYEAR FUELMAX PERFORMANCED

Customer Adaptations

CA No.	Description	Change Description
ADB90715	ADB, IN S99347 05 220120 Order change after final order to factory (*)	
S9001331	Frame mounted roof spoiler on tractor with fifth wheel. (*)	Show
S91516	Cab colour solid Coca Cola Red (FLD 3013)	
S99347	Factory delivery FCA (Free carrier incoterms 2000) (*)	Show

(*) **IMPORTANT:** If order is built with customer adaptations, final specification may differ from the information presented here, please check with [local support](#) or [TSSC](#) for further information.

 Latest updates

Technical Specification

Variant	Description	Administration
S1Q-01Q	Sid software for Android Auto	
S1Q-03Q	Sid software for Settings	
S1Q-06Q	Sid software for SEM update service	
S1Q-07Q	Sid software for Camera Stomp Service	
S1Q-08Q	Sid software for Trip Computer	
S1Q-09Q	Sid software for Drivers Handbook	
S1Q-0CQ	Sid software for alarm clock settings	
RT-STEEL	Steel rims on all axles	
F315-70A	Front axle tubeless tyre 315/70R22.5	
S2Q-Z1X	Without Service Offer voice control	
D315-70A	Drive axle tubeless tyre 315/70R22.5	
UPHTRI22	Textile interior trim level – Dynamic (FH)	
UOFFROAP	Without construction package	
UMBPAAC	Without market business package	
ESH-REAR	Horizontal muffler, rear exhaust outlet	

UELFPACK	Fuel package for EU6
FH-HSLP5	FH Globetrotter sleeper cab
UENOPT	Without energy optimization package
2LIVING	Living package 2 persons
INFOMED	Information package, medium
AIRFLOW	Air flow package including roof & side air deflectors and chassis skirts
UPVW	WITHOUT PVW VARIANT
RH-MTR	Roof hatch - Manually operated / Tinted glass / Rear opening
D13 500S	Diesel engine with Turbo-S, 12.8 litre Euro 6 SCR + EGR (Diesel Particulate Filter), 500 hp, 2500 Nm
L900A71B	Left 900 litre aluminium 710 mm high D-shaped diesel tank with two steps (cut out un chassis skirt)
R405A71	Right 405 litre aluminium 710 mm high D-shaped diesel tank
MIRCFPCS	Electrically heated and operated rear view mirrors
DRIVE5	Driving package
1DAYDIG	One day digital tachograph, EC approved
UKR-MSP	Ukraine
SS21W37	PRICELIST PERIOD 21W37-21W48
FH13B42T	FH 42 T ENG-VE13
SERIALPR	SERIALPR
UASAFE	Without active safety package
FH42T500	FH 500 HP 4*2 Tractor
4100CEN	4100 Central East North
VIS5+	Visibility Plus package for FH and FM.
MEDIAIR	Medium chassis height with rear air suspension
EUDRPA1	EUD ADJUSTMENT VARIANT (ONLY ENG-VE13)
EUDPAD13	DNP ADJUSTMENT EURO4 D13 BLOCK 637
EPAH342	EUD ADJUSTM FH13 42
EUDPEU5M	DNP adjustment Euro V mandatory
ULSA	Without local sourcing
SWUR	REMOTE SOFTWARE UPGRADE ENABLED
DRUT2	My Truck connects the vehicle to the smartphone app, 2 year prepaid subscription
TMROOFSP	Transport mounted roof spoiler, in cab or on frame.
S9001331	Frame mounted roof spoiler on tractor with fifth wheel.
S99347	Factory delivery FCA (Free carrier incoterms 2000)
S91516	Cab colour solid Coca Cola Red (FLD 3013)
RESERM	Remote service message
SERVIN-B	Service Instruction B
UOFFROAD	No offroad requirements
LSR	Lighting and signaling requirements according to ECE R48
MDR	Masses and dimensions requirements acc. to 1230/2012
BPR3	Brake performance requirement according to ece r13-11
EPR	External projection requirement according to ECE R61
TC-LONGD	Long distance transport cycle (driving pattern)
UDFVH	Without dynafleet vehicle status service
MFACTBEL	Main Factory Belgium
PVTS5	Map based preview topography service, 5 years prepaid subscription
EU6SCR	Euro 6 emission level with SCR, particle filter and EGR
DF-FUEL1	Dynafleet Fuel & Environment service, 1 year prepaid subscription
UDFDTM	Without Dynafleet Driver Times service
DF-POS1	Dynafleet Positioning service, 1 year prepaid subscription
UDFMSG	Without Dynafleet Messaging service
8EE	Market area East Europe
WB3800	Wheelbase 3800 mm
NEWHDV	New Heavy Duty Vehicle, Volvo (Will be deactivated after all factory intro ready)
24-HDV	New generation Volvo heavy vehicle
FH 42 T	FH 4x2 Tractor
DIRT-HIG	Much dirty roads/surfaces
EGR-H	Exhaust gas recirculation, hot
TYPE-FH	FH High tilt cab
UWVTAPPR	Without Whole Vehicle Type Approval, EC
4*2	4*2 - Two axles, rear axle driving
TRACTOR	Tractor model
RC-SMOOT	Smooth road conditions
GCW44.0	Gross combination weight 44.0 tonnes
ENG-VE13	12.8 litre six cylinder engine
VH4.0	Total vehicle height max. 4.0 metres
RAL13	Rear axle load 13 tonnes
STWPOS-L	Left hand drive
VW2600	Vehicle width 2600 mm
FAL7.5	Front axle load 7.5 tonnes
USWIPTO	Without pto switch type
USWIAUX	Without auxiliary switch type
UADR	Without ADR adaptation (transportation of dangerous goods)
MA-BAS	Basic market adaptation
CHH-MED	Chassis height medium - approx. 900 mm above ground level
UDFVSR	Without safety service subscription
ALT12500	Altitudes up to 2500 metres above the sea level
J1E-ABX	PROCESS B FOR NEW 24-HDV
COG-BAS	Complete superstructure & payload centre of gravity between 0.5 m and 1.0 m above top of truck frame
CURV-L	Low curve density (the speed is seldom reduced due to driving in curves)
VUPT-A2	Vehicle uptime, automatic service activation, weekly download, setting 2

NR-RQ03	External noise requirement, ECE R51.03 phase2, only EU6 + Austria noise in combination with SIGN-L
DTECH-CO	Combustion driveline technology
EFC-LQ	liquid fuel
UADRC	Without ADR classification
LEGC	Legislation check enabled for order
B-VANB	Box body / Van body / Curtainsider (non-insulated walls)
ULHE1	Without tail lift
ULHE2	Without crane
ULHE3	Without snow plough
ULHE4	Without miscellaneous load handling equipment
T-FLAT	Flat topography
VASSIS2	Vehicle assistance service enabled, with voice channel
S0Q-01Q	Sid software for Load Indicator
S0Q-06Q	Sid software for Parking Climate
S0Q-07Q	Sid software for TomTom navigation app
LFUEL	FICTIV VARIANT LEFT HAND FUELTANK (ALL SIZES)
RFUEL	FICTIOUS VARIANT RIGHTHAND FUELTANK (ALL SIZES)
UWVTA	Not Whole Vehicle Type Approved

ENGINE WITH MOUNTING AND EQUIPMENT

Variant	Description
DRC-AUTO	Regeneration control of diesel filter particulates - fully automatic (in motion)
OBDEP-E	EU6 mandatory on board diagnostics, phase E regulations
CSPED85	Pre defined maximum road speed limit, 85 km/h
USPLIMS	Without speed limiter sensor
SCRS-EHH	Electrically heated SCR system equipment
UFUELB	Without fuel blend
PADB80	80% AdBlue filling in tank
ULFFUEL	Without diesel plastic fueltank
CPSR-VAR	Variable coolant pump speed ratio
EASO-H	Horizontal orientation of the aftertreatment system
UTFUEL	Without temporary diesel tank
ADB100	AdBlue tank usable volume 100 litres, 710 mm high mounted on chassi side.
FUEFE2LW	Large engine mounted dual fuel filter with water separator and drain. For poor fuel (outside WestEu)
UXFUEL	Without extra fuel filling
ATL40	Ambient temperature down to -40 degrees C
ISD01	Engine idle shut-down after one minutes
ATU40	Ambient temperature up to +40C
FUFF-AS	Fuel filling anti-spillage device
UFUEQWH	Without fuel line heater
DIESEL	Diesel fuel
TURBO-S	Turbo single stage
UETEC	Without engine temperature control - Extreme conditions
BUGNET	Radiator screen / Mosquito net (PVC coated fibreglass) in front of radiator
D13K500	Diesel engine, 12.8 litre Euro 6 SCR + EGR (Diesel Particulate Filter), 500 hp.
ETOR2550	Engine torque range 2401 - 2550 Nm
EBR-VEB+	Volvo Engine Brake, VEB+ (high efficiency compression brake with exhaust pressure governor, EPG)
EAP-LHD2	Light heavy duty engine application (std pistons and corrosion resistant valve seats)
UENVIN	Without environmental incentives
RFN-B	Filler neck rear of the fuel tank
AF-R	Hot fuel recirculation heated fuel filter
RFUEL405	Right fuel tank 405 litres
USPEEDDU	Without dual speed limiter
SPEED90	Road speed limiter setting 90 km/h, EC
CRUIS-E	I-Cruise cruise control, I-Roll included
AIRIN-HI	High air intake
ULGAS	Without left side gas tank
K8F-C5X	Engine control unit EMS2.4
A-FREE25	40/60 mix coolant and water (-25°C, -13 °F)
FUELTS71	D-shaped 710 mm diam fuel tank
TNK-DUAL	Dual mounted fuel tank
FTANK-AL	Aluminium fuel tank
FCAP-L	Lockable diesel and AdBlue tank caps
STRAP-P	Painted fuel tank straps
UEXST	Without vertical exhaust
EXD-REAR	Exhaust direction, rear
UEXSH	Without extra exhaust heat shield
EAS-SD	Selective Catalyst Reduction + Diesel Particulate Filter, ceramic
EM-EU6	Emission level Euro 6
ACL1ST-S	Air cleaner with additional filter element (primary + secondary)
13PES3	Performance specification for 13 liter engine - No3
PRIM-MAN	Manual priming pump for fast and easy bleeding of the fuel system
FTCL-BAS	Fuel tank with basic ground clearance
UWILDBAR	Without wild bar
UFTI	Without fuel tanks interconnection
OILS-ST	Steel oil sump
TURB-HD	Turbo heavy duty design
HS-BAS	Basic muffler heat shield for all emission variants
CCV-OX	Open crankcase ventilation with oil separator and a maintenance free gas centrifuge
ADTP-R	AdBlue tank on right hand side
UADTC	Without AdBlue tank cover

OBDEC1 High emission level consequences
URSPED Without remote speed limiter

ELECTRIC POWER SUPPLY, LIGHTING, INSTRUMENTS

Variant	Description
UBATTC	Without battery charger
UAMPL	Without external amplifier
CL-STAT	Cornering lights
BAMAFREE	Enhanced flooded batteries extra
UBEPREP	Without body builder software electrical preparation
UWLC	Without working lamps back of cab
TD-LED	Trailer detection with LED sensor
AHS-LB	Automatic headlamp switching between day running light and low beam
UBBCHAS	Without Body builder electrical interface
TLB-BAS3	Fender mounted tail lamp bracket
ANT-CBR	Roof mounted antenna and cables for CB radio
SPK-DDR	Loudspeakers in dash, doors & rear
UAESW	Without Body builder electrical switches
TGW-4GWL	Telematics gateway with 4G modem and WLAN
UHLPPRO	Without headlamp protection
UREMCON	Without wireless remote control
USWARN	Without speed warning system
BUPALARM	Reversing warning unit (back-up alarm)
ARL-FLEX	Two (driver and passenger side) reading lamps with flexible arms and led lamps fitted on side walls
UINFOT	Without TV mounting preparation kit
UBUPMON	Without back-up monitor
UDRID	Without telematics driver ID with USB
ULSS	Without lane keeping support
LCS	Lane Change Support
UBLOG	Without diagnostic bodywork
UARSL	Without additional road speed limit
AUDWB1	Audio wavebands FM 87,5-108,0 MHZ, AM 522-1611 KHZ
UMAPR	Without map region for navigation
CO-USB3	Communication connector, usb, 3 ports
BULBKIT	Bulb and fuse kit
ULAMPIN	Without inspection lamp
UTSE	Without transportation security system
USPOTP	Without spotlamp preparation
SINF-C	Convenient service and infotainment level
BATS-S	Single energy battery storage system (2 batteries)
LOADIND	Load indicator with dashboard display
TAMA-B	Tachograph preparation kit for basic market area
UALARMB	Without burglar alarm
UAUXSW	Without wiring for extra switches
URCS	Without remote campaign settings
INST-HIG	Instrumentation, high performance 12" fully dynamic instrument cluster. Chrome surrounding
AUD-HIGH	Radio with multi format capacity, service and infotainment
BATTIND	Battery voltage, ampere and battery status gauge with visual alerts
UEXSTER	Without support for external steering control via body builder module
DRL-LED	V-shaped ("V-light") day running light (LED)
SID-HIGH	Dashboard integrated 7 inch colour information display, 800 x 480 pixels / 153(W) x 92(H) mm
FROM-PS	Front Monitoring connection, class VI for front angle camera in the lower mirror housing at the passe
EW73800	Equivalent wheelbase turning, 3800 mm
BLIGHT-E	Emergency brake light
BATTREC	Battery reconditioner to keep the battery lead plates free from sulphate
URPLCR	Without rear position lamp
BBOX-EF	Battery box at end of frame (single batt syst). Starter battery box on LH side when dual batt syst).
2BAT210C	AGM batteries 2x210 Ah
24V	Electrical system 24V
UDAS	Without Driver Alert Support (without drowsy driver warning)
HHL-ASYMR	Headlamp alignment set for right hand traffic
DETECT-S	Smoke detector in cab
HORN-ELS	Single electrical front horn
HORN-F1S	One front mounted (behind grille) single tone air horn, Jericho. Operated by steering wheel buttons.
URTOLL	Without road toll equipment
SOL24S	Single 24V/10A outlet in sleeper compartment
UFMS	Without fleet management system gateway
TWEETER	Tweeter
ECBB-BAS	Body builder electrical centre without any body builder module
POSLMP-W	Two white front roof mounted position lamps (end outline marker lamps, LED on FH)
AUDS-A	Audio signal - AM/FM
UASL	Without spot lamps in sign box
WWF-ALC	Windscreen washer fluid with alcohol additive
WL-TA1W	Trailer arch working lamp LED, white
UWARNLIG	Without roof mounted beacon warning lamp
SPG-KM	Speedometer scale kilometres per hour
EST-AID	Engine start pre-heating element
TL-LED	LED tail lamps
MSWI-C	Chassis main switch - battery box placed toggle switch circuit shut down
FOGL-WC	White front fog lamps
UDRIVL	Without auxiliary front driving lamps

UAUXL	Without snow plough preparation kit
HL-ADJA	Automatic adjustable headlamps to adjust the height of the light beam
<u>HL-CLEAN</u>	<u>High pressure headlamp cleaner</u>
<u>IMMOBIL</u>	<u>Immobiliser</u>
UIDLAMP	Without identification lamps
MARKL-SR	Side and rear marker lights
USRL	Without chassis working lamps
DRM-BE	<u>I-Shift drive mode balanced economy</u>
DIFL-RUS	Driver information first optional language Russian
DISL-POL	Driver information second optional language Polish
USAS	Without Service Alert System
<u>HL-LED</u>	<u>Led headlamps</u>
<u>24AL150B</u>	<u>Alternator 150 Ampere</u>
SI-GRAF	Speedometer instrument, tachograph
1DAY-STD	1 day tachograph, EC (standard)
CALI-DIG	Digital calibration of tacho. & speedometer
UNAVS	Without navigation system
UMCH	Without, monitoring connections chassis
UMCA	Without monitoring connections cab
BATTD128	Battery density, 1.28 acid solution
ASSIST4	Assistance switch and microphone, Volvo Action Service (VAS)
<u>HWSS-ACB</u>	<u>Adaptive cruise control with forward collision warning and emergency braking</u>
UARLIG	Without additional rear lights
<u>RSENS-W</u>	<u>Wiper rain sensor</u>
TAS-DIG	One day digital tachograph. EC approved, compliant with annex 1B regulation.
<u>INLI-NLD</u>	<u>Interior white and red (night) light with smooth light transition at on/off and dimmer</u>
URESTS	Without reflecting white stripes on chassis side
ACCLF-D	<u>Volvo torque assist - Disabled</u>
UALCOLOC	Without alcolock

POWER TRANSMISSION

Variant	Description
UASO	Without crawler gears
UTPTT	Without gearbox power take-off torque capacity
TTOR-B	Basic transmission output torque
UPTOTRA	Without PTO transmission
TPM-AUTR	<u>Transmission performance mode auto return</u>
TECOROLL	Transmission, Eco-roll
<u>AMSO-AUT</u>	<u>I-shift manual gear shift available in automatic mode incl kickdown function</u>
URSO	Without extra reverse gears
<u>AVO-ENH</u>	<u>Enhanced I-shift software for construction and off road applications</u>
<u>APF-BAS</u>	<u>Basic I-shift PTO functions</u>
PVT-MAP	<u>Map based topography information using a high resolution commercial topography map</u>
UEPTT	Without engine power take-off torque capacity
<u>TRAP-BAS</u>	<u>Basic gearbox application</u>
SRED-V	Single reduction rear axle
<u>RSS1352A</u>	<u>Rear single reduction solo axle - axle load 13 tonnes, GCW 52 tonnes, version A</u>
CS43B-O	<u>Single plate clutch, plate diameter 430 mm</u>
TRA-AMT	Automated mechanical gearbox
<u>GSS-AGS</u>	<u>I-shift lever gear selector</u>
<u>AT2612F</u>	<u>I-Shift automated mechanical 12-speed gearbox without clutch pedal, 2600 Nm, GCW 100000 kg</u>
TRAN-V	Volvo powertain gearbox
UPTER	Without rear engine mounted power-take-off
<u>TC-MWO</u>	<u>Basic performance cooler for manual/I-Shift gearboxes - water/oil</u>
UPTOENGR	Without rear engine mounted PTO
UPTOTR	Without gearbox driven power take-off
RAT2.47	Rear axle ratio 2.47
PROPS-M	Propeller shaft dimension medium, single joint
PSM3	Propeller shaft manufacturer Dana Spicer Compact+
DL-FULL	Differential lock between axles and wheels

BRAKE

Variant	Description
UCLUAIRC	Without clutchable air compressor
AIRT-GD	Airtank global design, EU
TEC-DET	Detachable trailer electric cable
<u>TBC-EC</u>	<u>Trailer brake connection, European Community</u>
TREL7-7	2x7 pol (24N+24S) electrical trailer connectors (UADR)
UPNPROT	Without protective cover for chassis mounted pneumatic equipment
TBH-COL	Long coiled trailer brake hoses (4000 mm)
<u>EBS-MED</u>	<u>EBS (Electronic Brake System) medium package</u>
UTRBSTRE	Without low speed automatic trailer brake activation (stretch brake)
PDC-IF	Pneumatic distribution center inside frame
UESPFC	Without ESP (Electronic Stability Program) functionality control
W8RA-NA	Weight ratio rear axle - not applicable (outside range)
UPBR	Without pusher brake
UPBRAD	Without pusher axle disc brake dimension
UTRACON	Without trailer light converter
UTABS	Without trailer ABS circuit converter
ATANK-ST	Steel air tanks
BF-DIBAS	Disc brakes with solid discs
BR-DIBAS	Rear brake disc, solid

BRA-D43	Front axle disc brake diameter 410 mm
UTBRD	Without tag axle brake
RBRA-D41	Driving axle disc brake diameter 410 mm
UTBRA	Without tag axle brake dimension
<u>DBRDUST</u>	Dust shield for rear brakes
<u>AUXPARK</u>	<u>Two extra parking brake chambers</u>
<u>BRAKE-DV</u>	Disc brakes
UATNKRUB	Without air tanks with rubber rings
URETARD	Without retarder
UAUXATNK	Without extra air tank
2COM1100	<u>Dual cylinder air compressor 760 cc / 1100 l/min</u>
TRBRAKE	Trailer brake valve
TCP-BMC	Trailer connection bracket (steel arch) mounted back of cab
TRBR-STA	<u>Stationary trailer brake control</u>
<u>ESP-BAS1</u>	<u>Electronic Stability Program (ESP) package 1</u>

WHEEL SUSPENSION AND STEERING

Variant	Description
PSP-VAR	<u>Power steering pump with variable displacement</u>
STW-D450	Steering wheel with diameter 450 mm
U1PAC	Without first pusher axle capacity
U1TAC	Without first tag axle capacity
<u>STWM-LE</u>	<u>Leather steering wheel</u>
UASFEE	Without Volvo Dynamic Steering
UTAXLE	Without tag axle
<u>RAD-GR</u>	<u>Rear air suspension, 1 axle - 1 driven</u>
RAA11	1 rear axle, 1 driven
FA-MED	Front axle medium ground clearance
FAA10	One front axle, not driven
URSTS	Without rear steering system
UACTST	Without active steering
UBL	Without bogie load sharing
UAUXPSP	Without extra power steering pump
URVCERT	Without vehicle certification, road
UBCYLPPO	Without brake cylinder protection
STG20.0	Steering gear ratio 20.0
PSS-SING	Single power steering system
<u>STGW-ADJ</u>	<u>Mechanically adjustable steering wheel, 2 motions</u>
ULDFA	Without load distribution on front axles
URALIM	Without first rear drive axle load limiter
ULIFT	Without bogie lift

FRAME, SPRINGS, DAMPING AND WHEELS

Variant	Description
<u>RFL1015</u>	<u>Rear frame length 1015 mm from 1st drive axle</u>
URUP	Without rear underrun protection
<u>FST-PAR</u>	<u>Two-leaf front parabolic suspension (normal stiffness)</u>
<u>RST-AIR</u>	<u>Rear air suspension</u>
FSS-LEAF	Front leaf suspension
RSS-AIR	Rear air suspension
FSTAB	Front stabilizer with normal stiffness
<u>SUP-BAS</u>	<u>Standard aluminium bars for side underrun protection</u>
RSTAB1	Rear stabilizer with normal stiffness
UFIL	<u>Without frame inner liner</u>
<u>SUSPL-EC</u>	<u>Air suspension levelling with electronic control</u>
WPRING-P	Painted wheel protection ring
WTDF22.5	Front wheel and tyre inner diameter 22.5 inches
WTDD22.5	Drive wheel and tyre inner diameter 22.5 inches
UWTDT	Without tag axle wheel and tyre inner diameter
WBD-MAX	Wheel brand drive, MAXION
UWBT	Without wheel brand trailing
UTWT	Without tag axle wheel type
UWTTM	Without tag axle wheel and tyre mounting
WMF-ST	Front steel rims
WMD-ST	Drive steel rims
UWMT	Without tag axle rim material
WDF900	9.00 inch front axle rims
WDD900	9.00 inch drive axle rims
UWDT	Without tag axle wheel dimension
<u>INFLAHOS</u>	<u>Tyre inflation hose</u>
UTIREPM	Without tyre pressure monitoring
UTT	Without tag axle tyre
TMF-GOOD	Goodyear front axle tyre
TMD-GOOD	Goodyear drive axle tyre
UTMT	Without tag axle tyre
TR-EUR	Tyre region Europe
URUPH	Without underrun protection
UFSL	Without air suspension levelling stroke
ASF-DL3	<u>Air suspension with 3 driving levels</u>
UGUARD	Without guard plate for cooling pipes and oil sump
<u>SWCP-T</u>	<u>Spare wheel transport mounted on top of frame</u>
SPWT-F	Spare wheel with tyre equal to front wheel

FSI-LEAF	Front leaf suspension
FTRR-A	Rolling resistance class A on front tire
DTRR-A	Rolling resistance class A on drive tire
WHA-BAS	Wheel attachment basic
UGAUGETP	Without tyre pressure gauge
UARSTA	Without additional rear stabilizer
URUPP	Without rear underrun protection position
UACMR	Without extra crossmember in rear overhang
WTA-TL	tubeless tyres
WSTUD-S	Short wheel studs (dual hole on aluminium rims)
UTMPR	Without pusher axle tyre
URFR	Without rear frame reinforcement
RSLS-BAS	Rear air suspension basic levelling stroke
XMBRR-B	Basic rear crossmember closing
UMRUP	Without rear underrun protection
FSM-MF	Maintenance free front suspension
WCAP	Wheel caps
HUBCOV	Hub cover that protects the drive shaft
USUPS	Without steps in side underrun protection
UTRTT	Without tag axle tyre tread
UPTT	Without pusher axle tyre tread
FUP	Front underrun protection
UWTDP	Without wheel and tyre diameter on pusher axle
UFRF	Without frame rail clearance
RSAP-BAS	Standard rear suspension application (without reinforcements)
UWTPM	Without wheel & tire mount pusher axle
UFALIM	Without front axle load limiter
PROTC-I	Improved corrosion protection level
UTWP	Without pusher axle wheel type
UWDP	Without pusher axle wheel dimension
URESTRUP	Without reflecting red stripes on rear underrun protection
UFRACLOS	Without frame end closing
TXMB4827	Transmission crossmember web location (main 4827)
RFEC-B	Rear frame end, bent (standard for tractor vehicles)
XMBT-B	Basic transmission crossmember
FST7575	Frame section thickness - web 7.5 mm / flange 7.5 mm
FRAME266	Frame rail section external height 266 mm

BODY, CAB AND INTERIOR

Variant	Description
ULPHF	Without front license plate holder design
FMUDE-TH	Front mudguard extension, tyre height dependent
CSPL-BXD	Storage drawer in lower center dash panel
ARU-BAS	Vinyl armrest upholstery
GRABHI-B	Instep grab handle, basic
UCPR	Without cab roof protection
UCLEQ	Without extendable windscreen cleaner
USEATV	Without ventilated seat
BUMP-SP	Front bumper spoiler
UTBL	Without toolbox on the left hand side
UTBR	Without right toolbox
USBPREDS	Without driver seat belt pretensioner
JACK-15T	Jack 15 tonnes
TOOL-BAS	TOOL-BAS Basic tool kit It is fitted in the storage compartment behind the left seat
URUSTP	Without transport rust protection (wax) except for muffler strap connections
WARR300	Warranty booklet, 300 000 km
UEMBO	Without emblem options
DGLAS-H	Tempered door glass
UCOFMAK	Without coffee maker
USTUC	Without storage compartment under cab
UWRNLAMP	Without portable warning lamp
USBPREPS	Without passenger seat belt pretensioner
GLASC-H	Hydrophobic glass coating on side windows
NSCABCOL	Non standard cab colour
ULADDER	Without ladder back of cab
KEYF4336	Keyfob frequency channel 433.6 MHz
EMBL-MO	Mounted emblems
BOTH-DL	Two 1.5 litre bottle holders, 1 under dashboard centre section, 1 mounted to the under bunk drawer.
UMICROWV	Without microwave equipment
SUPH-T1	Seat upholst.-black striped text. insert, black smooth text. bolster&red(FH)/blue(FM)vinyl side ins.
UTABLE	Without foldable table
CABPT-R1	One front cab roof pass through on passenger side
UWARVEST	Without warning vest
UAIRBAG	Without airbag
RUS-BAS	Rear cab upper storage 154 litres (300 mm high)
OLMAT-BA	Overlay mattress protector, 28 mm thick black textile
TELECARD	Volvo Action Service Europe (Blue telephone card)
WRITEPAD	Writing pad with spring-loaded paper clip
USIGNS	Without green and safe signs in front
RLS-BAS	Two storage drawers under bunk, totally 130 litres
VANMIR	Vanity mirror in front shelf lid



DIMATE	Dimension plate, EC
MATL-SF	Mattress lower bunk - semi-firm up to approx 100 kg, pocket springs.
DLAY-BAS	Basic dashboard layout
DTRI-SPE	Dashboard trim for FH
TOP2	Transmission oil STD 1273,07. Synthetic, thin oil. Needs filtering and cleaned transmission.
UCFAFS	Without foldable extra front cab foot-step
CUR1234Y	Climate unit refrigerant R1234YF
HCC-INEX	Lockable front hatch
SBD-BAS	Black safety belts, passenger and driver seats
SBP-BAS	Black safety belt, passenger seat
ADH-MED	Roof aerodynamic device height, medium
UCPARKC	Without cab parking cooler
UDECS	Without decal on cab side
ADCF-F	Additional flap on chassis fairings
AIDKIT	First aid kit
ISUNF-RM	Manual interior textile sun visor (roller-blind) integrated in front shelf
UAUXFS	Without extra footstep in cab side
CSPT-T	Center section dashpanel top, tray
UPUBS	Driver's handbook only in local language
EXTL-EN2	Exterior trim level enhanced 2
TBK70AD	Height adj. top bunk 700x1900 mm, foldable up to 52 degrees (dep. on cab & upper storage). Net incl.
UIDLMPSW	Without switch for identification lamps
UAWINDR	Without rear window
ROHO-MAN	Manually operated roof hatch
CSGN-GTR	GLOBETROTTER decal in the cab roof sign area
EMI-EMBL	Emission emblems
CAB-HSLP	High sleeper cab
RCABS-M	Mechanical rear cab suspension
CTILTP-M	Manual cab tilt pump
UADFS	Without extra DIN slots in front shelf (blind slots)
FMUD-AS	Mudflaps with spray suppression on all front-axle mudguards
USIDESTP	Without side foot-step and handle
FCABS-M	Mechanical front cab suspension
CURT-WIN	Windscreen and side windows curtains
UAWINDS	Without rear side window
WLIFT-AD	Electrical window lift, auto up/down driver side; el operated on passenger side
RHATCH	Roof hatch
GLAS-TIN	Tinted windows
LBK80FRM	Lower man manoeuvr recline bunk, foldable 55 degrees-2000x815/740/660mm (mid/head/feet). Safety net.
FMAT-RUB	Black rubber floor mats
PST-RX1	Passenger relax seat, swivel/tilt
CABH215	Cab height 215 cm
UACCBRT	Without roof-mounted accessory brackets
UREFS	Without reflecting stripes on cab
LANG-EG	English/German text on decals/signs
PUBL-RUS	Russian publication language
CERT-EC	Certification labels for EC countries (except DEU/FRA/GBR)
LOCK-REM	Central door locking with remote control
UREFL	Without reflectors
MAT-INS	Textile insert mat on engine tunnel
MIR-ELOP	Electrically heated and operated external rear view mirrors on both sides
AMIR-WB	Wide angle mirror on both sides
AMIR-F20	Front close view mirror above windscreen, passenger side (radius 200 mm)
TRIM-GN	Textile interior trim in matching grey nuances
ARMRE-BB	Two armrests on both driver and passenger seats
UROSIL	Without illuminated roof sign
DST-CF4	Driver seat, comfort, suspended, belt in seat
FIREXT3S	Fire extinguisher 3 kg, Swedish/English decal
PH-CAB2	Cab parking heater, 2 kW
AMIR-S30	Close view mirror on passenger side, radius 300 mm
ISUNS-DS	Manually manoeuvred side interior sun visor (roller blind type) on driver side
UAS	Without extra shelves in front rollfront compartments
CU-ECC	Fully electrically controlled air conditioning with sun sensor
UACU	Without additional climate unit
UDFHFP	Without Dynafleet Positioning+ service
BUMP-B	Plastic front bumper
TOWF-NO1	One front towing device
UWINREP	Without cab side window replica
USAFETYB	Without safety box
MPLA-ENG	Manufacturing plate, English version
SLCP-LUX	Luxury sleeper contr panel (int light, park heat/cool, hatch, lock, alarm clock, window, audio)
SUNV-H	Exterior transparent dark grey front sun visor
UXSEACAB	Without extra cab sealant material for dust tightness
AD-ROOF	Roof air deflector. Design aut. calc., varies dep. on vehicle tot. height (chassis, cab, tyres etc).
AD-SIDEL	Long cab side air deflector
AD-CHASX	Chassis side skirts
WARNTRI2	Two warning triangles
UMIRRTXT	Without mirror text
UETSBOX	Without engine tunnel storage box
REFRIG	33 litre under bunk mounted refrigerator with freezer and deviders

SIGN-L	L-sign in front (noise level 80dB)
XINS-CB2	One extra layer of extra thick (reinforced) cab insulation
UGUARDW	Without windscreen stone guard
UEBHEAT	Without electrical engine block heater

Miscellaneous

Variant	Description
UFFEND	Without fenders on second front axle
COD-UKR	Destination country Ukraine, national frequencies
CG-EU3	Destination country group Europe 3, national frequencies
URFCAR	Without rear fender carrier
RMUDF-AS	Mudflaps (anti-spray) on all rear-axle mudguards
RFEND-B	Three piece EC approved rear mud wings and spray flaps
FWP0675	Fifth wheel (king pin) position 675 mm before centre of first drive axle
5WM-ISOL	Fifth wheel ISO mounting on low L-profiles
5WH150	Fifth wheel leg-height 150 mm
KPSIZE50	King pin size 50 mm (2 inches)
5WT-JO8	Jost JSK 37 cast iron fixed fifth wheel
URAMP	Without sliding members/protection members
UTOWTYPE	Without towing member
UTOWMBR	Without towing member
UCOUPLIN	Without towing coupling
UTOWR	Without rear towing device
WHC-FOL2	2 foldable wheel chocks
RDECK	Basic rear deck (one plate between frame rails and one over left fuel tank or left battery box)
UTAIL	Without tail lift preparation
UHPG	Without gearbox mounted hydraulic pump
UFFTP	Without second front axle fender top height
UNIF-TRA	Basic tractor vehicle
ULCHF	Without load carrier
ULCL	Without load carrier length
RFC-1	Fender and front underrun calculation following EC legal requirements
RFH-BAS	Basic mudguard installation height on 2nd front axle and rear axles
5WLM-B	Basic fifth wheel maintenance
FACT-BEL	Final assembly plant Belgium
6100MM	Frame length 6100 mm
CHAGH-BL	Grab handles on chassis, black finish
UCHAINS	Without snow chains
UTMP	Without towing member position
UFFQP	Without second front axle quarter fender mounting position
UCROSSRE	Without cross reinforcement for swapbody
U5WLUB	Without fifth wheel lubrication
UTCIND	Without trailer connection indication
UHBAT	Without holes for body attachments
UHOOKSC	Without snow chain hooks
UPSCAT	Without propeller shaft catcher
UCRANEPK	Without crane plates
SDC1	Steering demand calculation according to ECE regulation R79
UFBA	Without front body attachments
URBA	Without rear body attachments
UHPE	Without engine mounted hydraulic pump
WHCP-F	Wheel chock(s) in the front part of the vehicle

List of warnings/errors (2 messages):

	16002	(1) No data sheet found for model FH42T3A.
	20010	(2) Multiple matches for supplementary drawing 23339406.

No restrictions violated