

# MAN Truck & Bus SE



## Scope of delivery

Basic data		Weights	
Order number:	601773080	Gross weight:	26000 / 28000 / 28000
Vehicle number:	24S4207	1. Front axle:	8000 / 8000 / 8000
Vehicle variant:	TGS 26.400 6X2/4 BLS	2. Front axle:	0 / 0 / 0
Basic vehicle:	L24S SG 31	3. Front axle:	0 / 0 / 0
Status:	Ready for delivery	Leading axle:	7500 / 7500 / 7500
Planned delivery date:	01.02.2016	1. Rear axle:	13000 / 13000 / 13000
Change stop:		2. Rear axle:	0 / 0 / 0
		Trailing axle:	0 / 0 / 0
VIN:	WMA24SZZ0GW215687		
Engine number:	51543801114378		

Add/remove	Code	Description
------------	------	-------------

### Current scope of delivery

	001AA	steering arrangement, left
	005GW	Wheelbase 2600+1350 mm
	006CI	rear frame overhang 800 mm
	018D6	D2676LF47 engine - 400 hp/294 kW EURO 6 SCR - 1,900 Nm (2,100 with TopTorque) CR New
	021GP	Gearbox software MAN TipMatic® Profi (road deployment)
	022GS	MAN TipMatic® 12 23 DD gearbox
	023YB	Aluminium fuel tank 450 l left with step and 24 l AdBlue
	025MH	front axle VOK-09 dropped
	025ZA	leading axle LOL-08 dropped - not lifting
	026EC	front springs parabolic 8.0 t
	027AN	radiator and intercooler for up to 35 degrees ambient temperature
	028AM	air suspension rear
	02AAE	instrument panel km/h 'High-Line'
	030EE	steering wheel with height and inclination adjustment
	032AB	MAN BrakeMatic (electronic brake system)
	034NK	hypoid rear axle HY-1350
	035EZ	Hypoid axle ratio i = 2.71
	037AC	with differential lock in rear axle
	038GG	disc wheels 10 hole 9.00-22.5 on 1st FA TL
	038PG	disc wheels 10-hole 9.00-22.5 on 1st RA TL
	038SG	disc wheels 10-hole 9.00-22.5 on leading axle TL
	038XT	without spare wheel

Add/remove	Code	Description
	03KAA	fuel tank fitted
	042DM	Digital tachograph made by MAN
	045CA	MAN EasyStart for TipMatic
	04WAA	spiral line between socket and semitrailer
	050NF	L cab 2240mm wide, 2280mm long
	052AC	Storage box accessible from inside and outside - flap unlocked from inside
	058BC	seat coverings in high-comfort quality
	058NR	Air-sprung comfort driver's seat, with lumbar support, shoulder adjustment and heating
	059NA	co-driver's seat static, with longitudinal + seat back adjustment
	05NAE	front panel unlockable from inside
	080AE	door interior panelling washable
	116AE	visco fan
	118AC	air deflector to stop dust swirling
	118EK	Short mounting base (engine only)
	118MA	EDC engine regulation
	118TT	TopTorque (higher torque in the two highest gears, 11 and 12)
	119EH	General PTO parameterisation
	119NB	Emergency brake signal (ESS)
	122D4	PTO NH/1C without flange f=0.82 right lateral horizontal
	124AL	fuel filter
	124AT	Heated additional fuel filter / water trap
	124EA	fuel filter heating
	128EC	Pressure sensor for air spring bellows
	142AF	calibrate tachograph
	153KC	air conditioning system AC R134A with automatic temperature control without CFHC
	159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
	194AE	operator's manual in DUTCH
	201AS	air intake raised with dry air filter
	201FA	fine dust and pollen filter
	203EK	connection for external engine speed control (ZDR)
	203ER	Control module for external data exchange (customer-specific control module) with body functionality
	205AB	Two-cylinder air compressor 720 ccm
	206KB	Exhaust on right with bottom outlet
	208AL	regulated rocker arm brake (EVBeC)
	210AA	flame starting system
	211FF	single-plate clutch MFZ 430
	227AC	rear axle breather upswept

Add/remove	Code	Description
	230ER	front underride guard
	230XX	Without rear underride guard
	232HA	synthetic bumper with integrated airdam
	234AX	towing coupling ROCKINGER SK5
	236AF	cross member for trailer coupling
	245XX	without spare wheel holder
	256AF	steering wheel lock with immobiliser
	258ET	Emergency Brake Assist 2 (EBA2) can be switched off
	258HA	anti-lock braking system (ABS)
	258HB	anti-spin regulator (ASR)
	258NA	ECAS air suspension
	258TA	Electronic stability program (ESP)
	259CA	disc brake for front axle
	259CB	disc brake for rear axle
	260EC	digital axle load display in cab for air-sprung axles
	262AZ	2-line brake connection behind cab
	272FA	Entry lighting for driver and co-driver
	276AC	Armrests for driver's seat
	278EA	Air connection in cab
	278EF	Air lines and air gun
	280AC	wiring for tank truck to ADR
	280EC	Fly mesh guard before radiator
	280FB	Working platform with step and grab handle
	280HD	Engine start/stop device under front panel
	280KY	working platform extended up to fifth wheel coupling
	283FS	Cab mounts on coil springs for 'L,LX ,XL,XLX,XXL' cab
	303AX	Lockable tank fastener - 1 u. ventilated for master key system
	303CC	AdBlue lockable filler cap 1 pc.
	309AA	Beam throw regulator
	310CN	High-beam headlights and fog lights, also with cornering light
	310EE	Halogen twin headlights H7 for right-hand traffic
	310FA	2 spotlights on cab roof
	310HB	Daytime driving lights (ECE R87-compliant)
	311PK	ECAS parameter entry with additional circuit for suppressing the automatic levelling suspension system
	318AA	marker lamps
	318AK	lateral marker lights
	319AR	reading lamp for driver

Add/remove	Code	Description
	320AC	Switches and wiring for cargo space lighting
	321EC	Central locking
	324AC	Two-tone horn,electric
	324CA	Two compressed air horns on the cab roof/roof spoiler
	325AA	MAN Tronic (on-board computer)
	325EK	Language 1 'Dutch' for display in instrument panel
	325FE	Language 2 'French' for display in instrument panel
	326CR	Trailer socket for ABS behind cab
	326ET	Trailer socket, 24 V, 7+7-pole, behind cab
	326FZ	Socket in cab 12V 2-pole and 24V 2-pole
	327AF	Battery main switch, mechanical
	329CT	Two 12-V 175-Ah batteries
	329EZ	Battery box up to 230 Ah, compact
	329HC	Maintenance sign for batteries - 'maintenance-free'
	331CY	28V three-phase alternator 120A 3360W Longlife Eco
	339FM	Display in instrument panel for trailer data (axle load)
	339FP	Display on the dashboard for operating data
	33VAC	Engine capsule
	343AN	Acoustic warning system at end of frame for engaged reverse gear
	345AU	Maximum electronic speed limitation 89 km/h
	345EA	Cruise control
	346CA	charging pressure indicator
	350AB	MAN sound system
	350I L	MAN TeleMatics 2 GPRS 'MAN TeleMatics service pack must be completed separately'
	350I U	Infotainment package plus
	350LS	Antenna for GPS and carphone D/E-net, on cab roof
	350LY	Antenna for Connectivity Board module
	350NW	MAN Media Truck Advanced 12 V radio with navigation preparation
	3500W	SD card, navigation system, WESTERN EUROPE
	350PA	Infrared remote control for MAN radio
	350TJ	Hands-free functionality for one mobile phone (multi-function steering wheel and Bluetooth®-capable)
	351LE	Lane Guard System IV (LGS IV)
	351US	AUX-IN/USB in the instrument panel
	352CF	2 halogen revolving beacons on cab roof left and right
	352WS	Revolving beacon, yellow
	353CA	shunting light on step unit
	362AA	Stabiliser for rear axle

Add/remove	Code	Description
	363AA	Stabiliser for front axle
	365AA	Starting-off aid
	370CR	Air dryer, heated
	373AE	antifreeze effective down to -35 degrees
	376FA	1 bunk with storage space (with aluminium frame).
	376HA	Mattress for lower bunk
	376XK	Without Mattress for upper bunk
	380AC	Windscreen of laminated glass tinted
	380CA	Door windows tinted
	381AS	Cab rear wall with 2 tinted windows, centre and right
	381CE	All-roand curtain
	381XC	Without curtain before bunks
	384CD	Safety belt display, driver's side
	385AT	Side windows tinted behind B-post
	386AS	Mechanical lifting roof
	387AF	Electric door window lifters for driver and co-driver
	388AH	Roller blind for windscreen, mechanical
	388AK	Sun shade in front of windscreen
	389AC	handles left and right (on B-post)
	389AD	handles left and right (on A-post)
	390AT	Oddment box
	390CU	1 pull-out drawer in centre of dashboard
	390XN	without waste paper bins between the seats
	392AR	Kerb mirror, right, heated and electrically adjustable
	392CL	EU front mirror on co-driver's side
	392CY	Electrically heated and adjustable rear and wide-angle mirrors
	392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
	394ED	1 Fire extinguisher, Belgian, 3 kg
	400AH	mudflap front
	401CY	synthetic mudguards, 3-part, with mud flaps
	404AP	spray reducer
	405AC	Bonding set, separate
	405AK	hazard-warning sign
	405AR	Hazard-warning lamp
	407XX	Without jack
	411AF	2 chocks
	434CH	Smoking package

Add/remove	Code	Description
	491GF	JOST JSK 37 C fifth-wheel coupling, design height 185 mm with integrated lubrication
	493FZ	Kingpin to rear axle centre 935 mm
	493YZ	Pickup plate 40 mm, make JOST
	538AF	Carpeted engine tunnel
	542DA	International regulatory documentation (COC)
	542FC	anti-noise package 80 dB (92/97EEC)
	542NC	Registration as N3 vehicle, (GVW > 12t)
	600AC	Fittings for right-hand traffic
	798LF	Height over cab, unloaded up to 4000 mm

**Nationale Baugruppe**

**Nationale Subbaugruppe**

BE663	Transport naar België / Transport vers Belgique
BE685	Recytyre 8 banden

**Wheel**

**Front axle**

2 x MI 315/70R22,5 MW XZ3D TL 156/150 L
---

**Leading axle**

2 x MI 315/70R22,5 MW XZ3D TL 156/150 L
---

**Rear axle**

4 x MI 315/70R22,5 MW XD3D TL 154/150 L
---

**Colour**

**chassis**

graphite black RAL 9011 matt	- Water
------------------------------	---------

**wheels**

White aluminium acrylic RAL 9006	- Normal
----------------------------------	----------

**cab**

Pure white RAL 9010	- Normal
---------------------	----------

